

## PRODUCT DESCRIPTION

Sandy nitrile is, of course, known for its high abrasion resistance. It's also more elastic and form fitting compared to other nitrile coatings. It's excellent in oily situations and very good in wet environments for nitrile version

## Sandy Touch S102



## FEATURES

- .Seamless knit liner - Minimizes finger irritation due to seam interference
- .Polyester liner / Sandy nitrile coating - High level of tear and abrasion resistance, provide durability for longer wear
- .Sandy nitrile coating - Palm coated, sandy finish for exceptional grip in water, grease or oil
- .Low linting construction for minimal contamination
- .Excellent price allows you to keep your workers safe while reducing costs

## TECHNICAL DETAILS

Coating: Black Sandy Nitrile  
Liner: Blue polyester shell in 13 gauge

Abrasion Resistance	4
Cutting Resistance	1
Tear Resistance	2
Puncture Resistance	1
ISO Cut Resistance	X
Impact Resistance	X

## APPLICATIONS

- .Manufacturing
- .Automotive assembly
- .Oil industries for light-duty
- .Agriculture
- .Gardening
- .Maintenance

## PHYSICAL PROPERTIES

Size Available		6/XS	7/S	8/M	9/L	10/XL	11/XXL	
Total Length	A(CM)	22	23	24	25	26	27	
Palm Width	B(CM)	8.5	9	9.5	10	10.5	11	
Weight (per pair)	GRAM							

\*Tolerance of measurement  $\pm 5\%$



**Nantong Sheng Li Jie Safety Products Co., Ltd**

Factory Address: New Development Zone Of Ma Tang, Rudong County, Jiangsu Province, China  
Shanghai Office: Room C208, No.1, Xinpan Road, Xinqiao Town, Songjiang District, Shanghai, 201612, China  
<http://www.gloveslj.com> Email: [Sales@gloveslj.com](mailto:Sales@gloveslj.com) Phone: 021 67668258